

RECOMMEND PCB LAYOUT
TOLERANCE ±0.05

NOTE:

1. MATERIAL

1.1 INSULATOR: HI-TEMP THERMOPLASTICS
UL 94V-0, COLOR: BLACK/WHITE

1.2 TERMINAL: COPPER ALLOY

1~3u" MIN. AU PLATED ON MATING AREA,
TIN/LEAD ON SOLDER TAILS, BOTH OVER
NICKEL UNDERPLATE.

1.3 SHELL: SPCC

△ TIN/LEAD PLATED ALL, OVER NICKEL
UNDERPLATE; OR NICKEL PLATED ALL

RoHS Compliant

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1


DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ± 0.38
.XX ± 0.25
.XXX ± 0.08
ANG ±

PJECTION



ORDER INFORMATION

USB-PRWH-4A-LF
SERIES | | | LEADFREE
| | | 4 PIN A TYPE
| | | WHITE
| | | DIP 90°
| | | MALE

DESCRIPTION: USB A TYPE 4P PLUG R/A