



NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	RG-174 外被: 黑色	1pcs
2	CONN:	SMA 母頭	1set
3	CONN:	MMCX	1pcs
4	H. S TUBE:	3Φ*15mm F32 黑	2pcs
5			
6			
7			
8			
9			

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

MMCXSMA-1R1S174-E15C-LF

SERIES

LEADFREE

150mm

MALE TO FEMALE

RG174

RT/ST

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y