

J1		J2
P1	MARKING LINE	P1
P2	GRAY	P2
P3	GRAY	P3
P38	GRAY	P38
P39	GRAY	P39
P40	GRAY	P40
PIN ASSIGNMENT		

#### NOTE:

- 1.FLAT CABLE:UL2651 28AWG 20C TINNED AND STRAND COPPER WIRE  
P=1.27MM.INSULATOR:PVC,GRAY
- 2.CONNECTOR:40P IDC SOCKET CONTACT GOLD FLASH.  
INSULATOR:BLACK
- 3.CONNECTOR:40P DIP IDC  
INSULATOR:BLACK
- 4.ELECTRONIC TEST CONDITION:
  - 4.1 100% OPEN SHORT & MIS-WIRE TEST
  - 4.2 CONDUCTIVE RESISTANCE:1/MAX
  - 4.3 INSULATION RESISTANCE:1/MIN,DCSV

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

#### RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±


.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



#### ORDER INFORMATION

F3IP01-4040-ATxxx-LF

SERIES

LEADFREE

8C5:85mm

13C:130mm

40 TO 40 WAY

TOTA LENGTH  
FEMALE TO MALE

DESCRIPTION: 40P IDC W/SR/DIP IDC