

NOTE:

- 1.CARD INSERTION SPECIFICATION
  - A. CARD INSERTION DEPTH:31.1 MM.
  - B. CARD THICKNESS=0.7-0.8 MM.
- 2.READING CONTACT:
 

POSITION:ACCORDING TO  
ISO 07816-2 C1-C8.  
CONTACT FORCE:30-50 GRAM.
- 3.MATERIAL AND FINISH:
  - A. HOUSING: LCP UL 94-V0 COLOR: BLACK.
  - B. CONTACT:PHOSPHOR BRONZE.SELECTIVE PLATING 3"AU  
OVER 30-50u" NI MIN UNDERPLAT 100u"SN ONLY ON TAIL ZONE.
  - C. SWITCH: PHOSPHOR BRONZE.SELECTIVE PLATING 3u"AU  
OVER 30-50u" NI MIN UNDERPLAT 100u"SN ONLY ON TAIL ZONE.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±  
.X ± 0.25  
.XX ± 0.15  
.XXX ± 0.10  
ANG ±



ORDER INFORMATION

SCF-W36B-08-LF  
SERIES | | LEADFREE  
| | 08 WAY  
| | SWITCH OPEN  
| | HIGH 3.65mm  
| | 90°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: