

BOM:

項目	名稱	規格	電鍍(或顏色)	數量	備註
8	公頭護蓋	PE(高密度)	透明	1	
7	塑膠下蓋(新模)	ABS, UL94 V-0	SEE TABLE 1	1	
6	塑膠上蓋(新模)	ABS, UL94 V-0	SEE TABLE 1	1	
5	外殼下蓋	BRASS(H/2), T=0.30±0.02mm	吃錫線	1	
4	外殼上蓋	BRASS(H/2), T=0.30±0.02mm	吃錫線	1	
3	膠心(24V)	SEE TABLE 3	PANTONE Gray IC	1	
2	PIN 2	BRASS(H), T=0.50±0.03mm	SEE TABLE 2	4	
1	PIN 1	BRASS(H), T=0.40±0.03mm	SEE TABLE 2	4	

NOTE: All materials conform ROHS standard.  
 ELECTRICAL CHARACTERISTICS:  
 RATINGS: 3.0A  
 CONTACT RESISTANCE:  
 30mΩ Max.(Initial)  
 400mΩ Max.(After life test)  
 INSULATION RESISTANCE: 1000MΩ Min  
 DIELECTRIC STRENGTH: 750V AC/1 minute.  
 MECHANICAL INSERTION FORCE: 6.6kgf MAX  
 WITHDRAWAL FORCE: 1.0kgf MIN

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 X, ±  
 .XX ±  
 .XXX ±  
 ANG ±

PJECTION



ORDER INFORMATION

PWUB-MSxxVxx-044A-LF

SERIES | 05V | LEADFREE  
 | 12V | POWER 4 PIN+4 PIN A TYPE  
 | 24V | GR: GREEN  
 MALE | RD: RED  
 SOLDER | BK: BLACK  
 | BG: BEIGE

DESCRIPTION: