



PANEL CUT-OUT

**SPECIFICATION:**

- INSULATION RESISTANCE: OVER  $100M\Omega$  500V DC.
- DIELECTRIC STRENGTH: 2000V AC ONE MINUTE.
- Body Material: Black Glass-Fiber Thermoplastic . UL 94V-2~0
- FUSEHOLDER SUITABLE 5x20mm FUSE.

<b>Rating: AC 10A 250V</b>	
Mark	Safety Regulation
@	3C
<b>Rating: AC 6A 250V</b>	
Mark	Safety Regulation
cULus	cULus

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ±

PJECTION



**ORDER INFORMATION**

ACF-PQ4FSPE-03V-LF  
SERIES | | | | LEADFREE  
MALE | | | | VERTICAL TERMINAL  
TAB 4.8mm | | | | 03WAY  
EAR  
PANEL  
FUSE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com