



CABLE	DIM
A	90±5
B	87±5
C	85±5
D	80±5
E	305±5
F	300±5
G	295±5
H	290±5

P	COLOR	P2	P3
1	WHITE	4	
	WHITE		4
2	WHITE	3	
	WHITE		3
3	WHITE	2	
	WHITE		2
4	WHITE	1	
	WHITE		1

Note: the above wire sizes do not include conn at both ends.

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	UL1007 #22 WHITE	1PCS
2	WIRE:	UL1007 #22 WHITE	1PCS
3	WIRE:	UL1007 #22 WHITE	1PCS
4	WIRE:	UL1007 #22 WHITE	1PCS
5	WIRE:	UL1007 #22 WHITE	1PCS
6	WIRE:	UL1007 #22 WHITE	1PCS
7	WIRE:	UL1007 #22 WHITE	1PCS
8	WIRE:	UL1007 #22 WHITE	1PCS
9	HOUSING:	KK-H-04	3PCS
10	TERMINAL:	KK-T-18	12PCS
11	CABLE TIE:	NATURAL COLOR 2.5*100mm	4PCS
12			

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司  
www.morethanall.com

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE  
SIZE A4 PPROJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

KKX12-0404RR22-F27C-LF  
SERIES  
LEADFREE  
270mm  
FEMALE TO FEMALE  
22 AWG  
04 TO 04 WAY 90°/90°

DESCRIPTION: