



P1	2	BROWN	1	P5
	4	ORANGE	2	
P2	2	BROWN	3	
	4	ORANGE	4	
P3	2	BROWN	5	
	4	ORANGE	6	
P4	2	BROWN	7	
	4	ORANGE	8	

P1	1	BLACK	9	P5
	3	RED	10	
P2	1	BLACK	11	
	3	RED	12	
P3	1	BLACK	13	
	3	RED	14	
P4	1	BLACK	15	
	3	RED	16	

WIRING TABLE

Electronics Test :

1. Contact Resistance : 3 Ω Max.
2. 100% open & short test (set at 50 KΩ)
3. At DC = 300V , Insulation Resistance : 20 MΩ Min.
4. Test Condition : Temperature : 25 ± 5°C , Humidity : 50% RH Max.

6	LABEL, WHITE (MARKING, BLACK)	4 PCS
5	CABLE TIE, TRANSPARENT WHITE	6 PCS
4	SOCKET CONTACT	32 PCS
3	HOUSING, 16-POS, 4.20mm PITCH, TRANSPARENT WHITE	1 PC
2	HOUSING, 4-POS, 4.20mm PITCH, TRANSPARENT WHITE	4 PCS
1	CABLE, 18 AWG x 4C + A, UL 2464, BLACK	A/R
ITEM	DESCRIPTION	Q'TY

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

MFX14-B08B0218R1S1-F1M-LF  
SERIES | LEADFREE  
16 TO 04 WAY | 18 AWG | SHIELD  
FEMALE  
ROUND CABLE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com