



**DGC 15 M/F GENDER CHANGER**

**PIN OUT: 15Male**

**15Female**

|    |       |    |
|----|-------|----|
| 1  | ----- | 1  |
| 2  | ----- | 2  |
| }  |       |    |
| 14 | ----- | 14 |
| 15 | ----- | 15 |
| G  | ----- | G  |

Label: yellow color with black character  
 One side: MINI GENDER CHANGER

The other side: U.S.A. PATENT 5199906 GENERAL CHANGES

**SPECIFICATION**

**INSULATOR:** PBT Glass fibre reinforced UL 94 VO

**CONTACT:** Brass

**CONTACT PLATING:** Gold plated over nickel

**SHELL:** Tin plated shell

**CURRENT RATING:** 3 AMP

**DIELECTRIC STRENGTH:** 1000V AC for one minute

**INSULATOR RESISTANCE:** 1000MΩ min at 500V DC

**TEMPERATURE:** -55°C — +105°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

P PROJECTION



**ORDER INFORMATION**

**DBX2-ES-1515-LF**

SERIES

LEADFREE

15 TO 15 WAY

MALE TO FEMALE

**煜倫股份有限公司**

[www.morethanall.com](http://www.morethanall.com)

DESCRIPTION: