

- Material:
- Item ① Lever: Thermoplastic (UL 94V-0)
 - Item ② Terminal housing: Thermoplastic (UL 94V-0)
 - Item ③ Wire guard: Stainless steel
 - Item ④ Solder Pin: Brass.Tin plated

- Electrical: cULus
- Voltage rating: 300 V
 - Current rating: 10 A
 - Wire range:
 - Solid wire(AWG): 16-24
 - Stranded wire(AWG): 16-24
 - Wire strip length: 12-13 mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval:

N=NUMBER OF CONTACTS

DIM	TOL				
	2P--6P	7P--12P	13P--18P	19P--24P	
Dim L	N×3.5+0.70	±0.15	±0.20	±0.30	±0.40
Dim P	(N-1)×3.5	±0.15	±0.20	±0.30	±0.40

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1


.XXX ±

DATE

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

TBX035-R08-xx-LF

SERIES

LEADFREE

02~24WAY

HIGH 8.5mm

DIP 90°

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com