



ELECTRIC FUNCTION	DETECT SWITCH
WITHOUT CARD	OPEN
CARD INSERTED	CLOSED



### MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK  
 SHELL: STAINLESS STEEL  
 TERMINAL: PHOSPHOR BRONZE, GOLD PLATED ON CONTACT AREA TIN PLATING ON SOLDER TAIL

### SPECIFICATION

CURRENT RATING: 0.5 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -40°C~+85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 .X ± 0.30  
 .XX ± 0.20  
 .XXX ± 0.10  
 ANG ± 3°

PJECTION



ORDER INFORMATION

SCV-W2525XBR-06-LF

SERIES | LEADFREE  
 06WAY  
 REEL  
 OPEN SWITCH  
 NON POST  
 BODY HIGH 2.5mm  
 90°SMT  
 PAD TO PAD 25.54mm

DESCRIPTION: SIM CARD, 6PIN, PCB MOUNT, SMT, METAL SHIELD, FEMALE, HINGE TYPE WITH SWITCH

