

A	COLOR	B
1	RED	1
2	RED	2
3	BLACK	3
4	BLACK+BRAID	4
5	WHITE	5
6	GREEN	6
7	BLACK	7
8	WHITE	8
9	GREEN	9
10	BLACK	10

A	COLOR	B
11	WHITE	11
12	GREEN	12
13	BLACK	13
14	WHITE	14
15	GREEN	15
16	BLACK	16
17	WHITE	17
18	GREEN	18
19	BLACK	19
20	BLACK	20

△ 1. Welding of black wire and braided mesh.  
 2. Use solder  
 The solder joint is wrapped in the acetate cloth at both ends.

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	UL/CSA 1571 #28 OD:0.60 RED	2pcs
2	WIRE:	UL/CSA 1571 #28 OD:0.60 BLACK	2pcs
3	WIRE:	UL/CSA 1571 #28 OD:0.60 BLACK	12pcs
4	WIRE:	UL/CSA 1571 #28 OD:0.60 WHITE	5pcs
5	WIRE:	UL/CSA 1571 #28 OD:0.60 GREEN	5pcs
6	HOUSING:	DF19-H-20	1pcs
7	TERMINAL:	DF19-T-28	20pcs
8	HOUSING:	MPVK-HD-2X10	1pcs
9	TERMINAL:	MPVK-T-28	20pcs
10	BRAID:	0.12*168	1pcs
11	SHRINK TUBE:	2.5ø*12mm F32 BLACK	2pcs
12	Acetate TAPE:	W:30*L:40 BLACK	2pcs

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PPOJECTION



ORDER INFORMATION

DF19MPVKD-202028EB1-F25C-LF

SERIES

LEADFREE  
 250mm  
 FEMALE TO FEMALE  
 BRAID+GND  
 28 AWG  
 20 TO 20 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y