

T:1.6 Dimensions of PC board holes  
Tolerance :±0.05(Printed-top view)

SCHEMATIC				
PJ-R12M-05C	PJ-R12M-04R	PJ-R12M-04L	PJ-R12M-03	PJ-R12M-03B

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

9	SPRING	2	SWC WIRE	
8	HOUSING	1	PBT 4815	UL-94V0(BLACK)
7	COVER	1	PBT 4815	UL-94V0(BLACK)
6	AXIS SUPPORT	1	H59(COPPER ALLOY)	Ni PLATED
5	CURVE PIECE	1	C2680 t=0.30	Ag PLATED
4	CURVE PIECE	1	C2680 t=0.30	Ag PLATED
3	SPRING PIECE	1	C5191 t=0.30	Ag PLATED
2	SPRING PIECE	1	C5191 t=0.30	Ag PLATED
1	FLAT PIECE	1	C2680 t=0.30	Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±

PPOJECTION



ORDER INFORMATION

PJ-R12M-xxx-LF  
SERIES | | | LEADFREE  
SCHEMATIC  
METAL  
HIGH 12.4mm  
DIP 90°

DESCRIPTION: MINIATURE JACK