



✓	Poles	A±0.30	B±0.20		17	85.98	80.0
	02	10.98	5.0		18	90.98	85.0
	03	15.98	10.0	↓	Poles	A±0.45	B±0.35
	04	20.98	15.0		19	95.98	90.0
	05	25.98	20.0		20	100.98	95.0
	06	30.98	25.0		21	105.98	100.0
↓	Poles	A±0.35	B±0.25		22	110.98	105.0
	07	35.98	30.0		23	115.98	110.0
	08	40.98	35.0		24	120.98	115.0
	09	45.98	40.0	↓	Poles	A±0.50	B±0.40
	10	50.98	45.0		25	125.98	120.0
	11	55.98	50.0		26	130.98	125.0
	12	60.98	55.0				
↓	Poles	A±0.40	B±0.30				
	13	65.98	60.0				
	14	70.98	65.0				
	15	75.98	70.0				
	16	80.98	75.0				

Screws Torque: 7.0 In-Lb  
 Wire Range: 16~22 AWG  
 Rated: 10 Amperes.AC250V  
 Operation Temperature: -55°C~+100°C  
 Insulation withstands volt: AC2000V min  
 Insulation resistance: >2000MΩ/DC500V

	Material	Plating/Finish	Remark
A	Insulating body	PA66 UL 94V-0	Green
B	Terminal	Brass	Tin
C	Screw	Steel	Yellow Zinc
D	Spring:	Steel	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 X, ±  
 .XX ±  
 .XXX ±  
 ANG ±

P PROJECTION



ORDER INFORMATION

TBN050-D11-xx-LF

SERIES | LEADFREE  
 02~26WAY  
 HIGH 11.0mm  
 DIP180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: