

NOTES:

***Material**

Body: Nylon46/Nylon66,UL 94V-0 Rated.
 Plastic Ear: Nylon66,UL 94V-2 Rated.
 Spring: 65Mn.
 Contacts: Brass
 Plating: Au plating on contact area;
 Sn(100u" Min.) plating on solder tail;
 Ni(50u" Min.) underplating overall.

***Mechanical:**

Insertion Force: 1.15N max per contact pair;
 Withdrawal Force: 0.15N min per contact pair;
 Contact Retention Force: 3.43N min per contact;

***Electrical Specification**

Contact Resistance : 30 Milliohms Max.
 Current Resistance : 1.1 Ampere
 Insulation Resistance : 1000 Megohms Min, At 500V AC.

***Environmental**

Operating Temperature : -55°c to +105°c



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm

SCALE 1:1


DATE

SIZE A4

TOLERANCES ARE

X, ±
 .X ± 0.35
 .XX ± 0.25
 .XXX ± 0.15
 ANG ± 3°

PJECTION



ORDER INFORMATION

PCIX-DLS-164-LF

SERIES | LEADFREE
 164WAY
 SLID LOCK
 DIP 180°

DESCRIPTION: PCI Express 164 Pin Connector
 Clamp Right Side Type(Plastic Posts)