


Specifications:
 Current Rating:1.0A AC/DC
 Voltage Rating:30V AC/DC
 Contact Resistance:20m ohm. Max.
 Insulation Resistance:1000M ohm. Min.
 Withstanding Voltage:AC 500V AC/minute
 Operating Temperature Range:-40°C ~ +105°C
 Material and Finish
 Insulator:High Temp. Plastic(Nylon 46 UL94V-0)
 Insulator Color:Red
 Contact material:Phosphor Bronze
 Finish:Tin Plated

Pos	A	B	C	Pos	A	B	C
4	7.00	3.81	5.60	16	22.24	19.05	20.84
6	9.54	6.35	8.14	18	24.78	21.59	23.38
8	12.08	8.89	10.68	20	27.32	24.13	25.92
10	14.62	11.43	13.22	22	29.86	26.67	28.46
12	17.16	13.97	15.76	24	32.40	29.21	31.00
14	19.70	16.51	18.30	26	34.94	31.75	33.54



PCB Layout

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±0.20

UNIT / mm

SCALE 1 : 1

.XX±0.15


DATE

.XXX±

ANG±

SIZE A4

PJECTION



ORDER INFORMATION

MIM-SVC-xx-LF
 SERIES | | LEADFREE
 | | 04~26WAY
 | | CAP
 | | 180°SMT
 | | FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.54mm PCB Connector SMD Type