

ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 3ohm max
3. Insulation Resistance: 10mega ohm MIN
4. Hipot test: DC 300V 10ms

| | | | |
|------------|-----------------------------|-------------|-------------|
| 4 | 4P CONN WHITE | 1 | pcs |
| 3 | 45P 黑色 PVC | 12 | G |
| 2 | DC 5.5*2.5 | 1 | pcs |
| 1 | AWG22/1C+S*2F OD:1.8*3.6 黑色 | 1 | pcs |
| NO. | Description | Q'TY | Unit |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

DCTBT-250222-E1F-LF

SERIES

LEADFREE

300mm

MALE TO FEMALE

22 AWG

2.5Ø TO 02 WAY

DESCRIPTION: DC5.5*2.5 TO 4P/Conn L=300mm