



NOTE:

1. Hi-Pot: 300V 0.1SEC
2. Conductor Resistance: 2 OHM MAX
3. Insulation Resistance 10M OHM MIN
4. 100% Open&Short. miss wire test

4	PVC	45P PVC Black	X
3	CONN	MIRCO USB 5P/M Black housing W/shielded	1PCS
2	CONN	USB AM White Housing W/Shielded G/F	1PCS
1	Cable	U12725 28AWGx1P+28AWGx2C+AEB OD:3.5mm L=1000mm Black	1PCS
No.	Item	Description	qty

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.50
.XX ± 0.35
.XXX ± 0.20
ANG ± 3°

PJECTION



ORDER INFORMATION

MIBUB-5B4A28-M1M-LF

SERIES

LEADFREE
1000mm
MALE TO MALE
28 AWG

5 PIN B TYPE TO 4 PIN A TYPE

DESCRIPTION: Micro-USB-5B PLUG TO USB-4A PLUG CABLE