



ELECTRICAL SPECIFICATIONS:
 VOLTAGE RATING:AC 500V
 WITH STANDING VOLTAGE:AC 1,000V ONE MINUTE
 INSULATION RESISTANCE:1,000MΩMIN AT DC 500V
 CONTACT RESISTANCE:3MΩ MAX AT DC 1A
 FREQUENCY RANGE:0-4,000MHZ
 VSWR:1.2MAX 0-4GHz

8	GASKET	SI-RUBBER	ORANGE	1
7	RETAINING	BRASS	NICKEL	1
6	SHELL	BRASS	NICKEL	1
5	FERRULE	BRASS	NICKEL	1
4	GROUND RING	BRASS	NICKEL	1
3	DIELECTRIC	DELRIN	WHITE	1
2	PIN	BRASS	GOLD	1
1	BODY	BRASS	NICKEL	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. ± 0.30
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ± 1°



ORDER INFORMATION

N-PC-213-LF
 SERIES | LEADFREE
 | RG213
 | CRIMP
 MALE

DESCRIPTION: N MALE CRIMP