



### Material

- Item ① Insulating body Thermoplastic (UL94V-0)
- Item ② Insulating body Thermoplastic (UL94V-0)
- Item ③ Insulating lever Thermoplastic (UL94V-0)
- Item ④ Wire guard Stainless Steel
- Item ⑤ Contacts PIN PhBz (CuSn) Tin plated
- Item ⑥ With flange screw Steel M2.5 plated zinc

### Electrical

- Voltage rating: 300V  $\Delta$
- Current rating: 8A  $\Delta$
- Solid wire(AWG): 16-28  $\Delta$
- Stranded wire(AWG): 16-28  $\Delta$
- Wire strip length: 8-9mm  $\Delta$
- Withstanding Voltage: 1.6KV  $\Delta$
- Operating temperature: -40°C to +115°C
- Safety Approval:



POLE	2	3	4	5	6
A	8.42	12.23	16.04	19.85	23.66
B	3.81	7.62	11.43	15.24	19.05
Tol.	±0.20				

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

SIZE A4

P PROJECTION



### ORDER INFORMATION

TBX038-SVCCF-xx-LF

SERIES | | | | LEADFREE  
02-24WAY  
FLANGE  
C TYPE  
FEMALE | CAGE  
SCREW 180°

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com