

PCB LAYOUT

Ref.

MATERIAL:

- HOUSING—DSM STANYL TE250F6 (NYLON—46)
BLACK COLOR, UL94V-0
- CONTACTS—0.35mm THICK PHOS—BRONZE
PLATED WITH HARD GOLD AND
GOLD FLASH IN SOLDER AREA.
- HOLD DOWN—0.30mm THICK COPPER ALLOY,
PLATED WITH NICKEL.

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±

DATE

.XXX±


ANG±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION



ORDER INFORMATION

MJW11-KX06-0404-LF

SERIES

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

4P4C LEADFREE
06u" GOLD
NON EAR
BLACK

DESCRIPTION: 4POSITION, SMT TYPE SIDE ENTRY PCB JACK