



PART NO	A±0.20	B±0.20	C±0.20	D±0.20
CS-S-36	67.69	59.74	48.90	36.72
CS-S-50	82.78	74.85	64.00	51.84

Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Front shell: Cold rolled steel,t=0.45mm,0.50mm,0.60mm
- 1.4 Back shell:Cold rolled steel,t=0.40mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Total mating force: 4.0 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.
- 2.7 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 contacts:Gold flashed 1u”
- 3.2 Shell: Nickel,tin or gold plated

7	Trangle	2	Cold Rolled Steel	T=0.60mm	Nickel Plated
5	Spring	2	Stainless	∅0.9	Nickel Plated
4	Back-shell	1	Cold Rolled Steel	T=0.40mm	Tin Plated
3	Front-shell	1	Cold Rolled Steel	T=0.45mm, 0.50mm,0.60mm	Nickel Plated
2	Contact	36	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Blue
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°



ORDER INFORMATION

CS-S-xx-LF
SERIES | T LEADFREE
36.50 WAY
FEMALE

DESCRIPTION: CENTRONIC SOLDER(F) 腳三角片