



PART LIST: 本产品均符合”ROHS”环保标准，用的材料均为相当品。

7	黑色套管 $\varnothing 4.5$ L=10MM.	1	PCS
6	TERMINAL: 2.54 端子.	5	PCS
5	HOUSING: 2.54mm PITCH -H-1*5P.	1	SET
4	六角螺母.	2	SET
3	OUTER MOLDED: 45P PVC BLACK.		Kg/1K
2	USB B F 焊线式 白胶芯 铁壳镀镍 PIN针G/F	1	SET
1	USB UL2725 28AWG*1P+24AWG*2C+AB OD: 4.5mm 黑色PVC.		MM
ITEM	STANDARD SPECIFICATION	Q' TY	UNIT

ELECTRONIC TEST:

- 100% TEST, (Open, Short, Miss Wire).
- Contact Resistance: 1 Ω /max.
- Insulation Resistance: 20M Ω /min.
- Hi-Pot: 300v dc/10ms.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. \pm

CHECKED BY GENIUS

.X \pm

UNIT / mm

SCALE 1:1

.XXX \pm

DATE

ANG \pm

SIZE A4

P PROJECTION



ORDER INFORMATION

PVUB-054BPE2428-F1M-LF

SERIES

LEADFREE

1000mm

FEMALE TO FEMALE

24, 28 AWG

PANEL EAR

05 WAY TO 4 PIN B TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: USB BF帶耳 TO 杜邦2.54 1*5P CABLE BALCK L=1000MM