

P.C.B. LAYOUT

1. MATERIALS AND FINISH

SHELL: STEEL MATERIAL, FRONT SHELL TIN FINISHED
 BACK SHELL TIN FINISHED
 DIMPLES ON PLUG ONLY

INSULATOR: PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0, BLACK
 CONTACT: COPPER ALLOY, FULL GOLD FLASH

2. SPECIFICATION

CONTACT CURRENT RATING : 5.0 A
 CONTACT RESISTANCE : 10 mΩ MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5GΩ MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

No	A	B	C
09	16.30	25.00	30.80
15	24.60	33.30	39.20
25	38.40	47.00	53.00
37	54.80	63.50	69.30

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
 .X ± 0.30
 .XX ± 0.25
 .XXX ± 0.15
 ANG ± 2°



ORDER INFORMATION

DR72-SZJ-xx-LF

SERIES | | | | | LEADFREE
 | | | | | 09-37 WAY
 | | | | | JACKSCREW
 | | | | | NUT
 | | | | | CLIP
 | | | | | FEMALE

DESCRIPTION: D-SUB 90°, FEMALE, L PIECE, 7.2 mm, Machine Pin