

PCB Layout (B)

● MATERIALS: (RoHS Compliant)

Housing: Plastic Thermoplastic  
P.B.T UL94V-0 Black

Contacts: Phosphor Bronze Gold  
Selective Plated

Front Shell: Steel Nickel Plated  
Over Copper

● ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 0.5 Amp

Dielectric Withstanding Voltage: 500V AC

Insulation Resistance: >500MΩ/Min

Contact Resistance: 35mΩ/Max

Operation Temperature: -55°C ~ +85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X.±  
X±  
.XX±  
.XXX±  
ANG±



ORDER INFORMATION

HPD-SDL-068-LF  
SERIES | LEADFREE  
| 68 WAY  
| LOCK  
| DIP 180°  
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 1.27mm(.050") Pitch D-SUB 68P Female  
Connector Straight Dip Solder Type