

NOTES

*Material

Housing: LCP, UL 94V-0 Rated; Color:Black.

Contact: Phosphor Bronze

Clip: Brass

Plating: Gold Plating Over Nickel on Contact Area;
Tin/Lead Plating on Terminal.

*Electrical Specification

Operation Voltage: 100 VAC Max.

Current Rating: 1.5 Ampere Per Contact

Contact Resistance: 30 Milliohms Max.

Insulation Resistance: 1000 Megohms Min.

Dielectric Withstanding Voltage: 500 VAC

*Environmental

Operating Temperature: -55°C to +125°C

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±


.X, ±

.XX, ±

.XXX, ±

ANG ±

PPOJECTION



ORDER INFORMATION

SATA-SV09Z-7+15-LF

SERIES
CLIP
HIGH 9.0mm
180°SMT
FEMALE
LEADFREE
7+15 WAY

DESCRIPTION: SATA 7+15Pins (直立式SMT 母座)