

PCB LAYOUT RECOMMENDED

Pin No.	Description
S1	Vcc(Voltage)
S2	RST
S3	CLK
S5	GND
S6	Vpp
S7	I/O

NOTES:

\*Material

Housing: LCP UL 94V-0, Color:Black;  
 Contact: Phosphor Bronze;  
 Plating: Au plating on contact area;  
 Sn (80u" Min.) plating on solder tail;  
 Ni (50u" Min.) underplating overall.

\*Mechanical


Durability: 3000 Cycles.

\*Specification:

Current Rating: 0.5A. 12V AC.;  
 Dielectric Withstanding Voltage: AC 500V For 1 Minute;  
 Insulation Resistance: 500MΩ Min.;  
 Contact Resistance: 100mΩ Max.;

\*Environmental

Operating Temperature: -20°C to +60°C;



RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ±  
 .X ± 0.20  
 .XX ± 0.10  
 .XXX ±  
 ANG ±

PJECTION



ORDER INFORMATION

SCV-W2523X-06-LF  
 SERIES | | | LEADFREE  
 | | | 06WAY  
 | | | NON POST  
 | | | BODY HIGH 2.3mm  
 | | | PAD TO PAD 25.2mm  
 | | | 90°SMT

DESCRIPTION: Sim Card 6Pin Without Post

煜倫股份有限公司

www.morethanall.com