



## SPECIFICATIONS

### Material

Insulator : PBT glass reinforced, rated UL94V-0

Contact : Phosphor Bronze

Strain Relief Hook : Phosphor Bronze

### Matching requirements

Wire : Flat ribbon cable pitch 0.635mm 30AWG

Insertion Depth : 2.60mm to 3.10mm

Lead Size Accedted : 0.40mm square

### Electrical

Current Rating : 1 Amp

Contact Resistance : 30m ohm Max.

Insulator Resistance : 1000M ohm min.

Dielectric Withstanding Voltage : 250V AC for 1minute

Operating Temp Range : -40°~+105°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

HAF-C2A-xxx-LF  
SERIES | | LEADFREE  
| | 006~080 WAY  
| | TYPE A  
| | TWO TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: