

Circuits	Dimension		
	A	B	C
10	10.0	25.9	8.0
12	12.0	27.9	10.0
14	14.0	29.9	12.0
16	16.0	31.9	14.0
20	20.0	35.9	18.0
22	22.0	37.9	20.0
24	24.0	39.9	22.0
26	26.0	41.9	24.0
30	30.0	45.9	28.0
32	32.0	47.9	30.0
34	34.0	49.9	32.0
40	40.0	55.9	38.0
44	44.0	59.9	42.0
50	50.0	65.9	48.0
60	60.0	75.9	58.0

Contact:  
 Contact:Brass.  
 Insulator:Nylon 9T.  
 Finish:Gold flash plated over nickel.


**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
 煜倫股份有限公司  
 www.morethanall.com

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±



**ORDER INFORMATION**

ML-D-xxx-LF  
 SERIES | LEADFREE  
 010-060 WAY  
 DIP 180°

DESCRIPTION: Shrouded Header2.0 Pitch Dual Row Straight (Short Lever)