

Pin 數	A	B	C	D	Pin 數	A	B	C	D
10	9.41	6.99	5.08	8.12	56	38.62	36.20	34.29	37.33
12	10.68	8.26	6.35	9.39	58	39.89	37.47	35.56	38.60
14	11.95	9.53	7.62	10.66	60	41.16	38.74	36.83	39.87
16	13.22	10.80	8.89	11.93	62	42.43	40.01	38.10	41.14
18	14.49	12.07	10.16	13.20	64	43.70	41.28	39.37	42.41
20	15.76	13.34	11.43	14.47	66	44.97	42.55	40.64	43.68
22	17.03	14.61	12.70	15.74	68	46.24	43.82	41.91	44.95
24	18.30	15.88	13.97	17.01	70	47.51	45.09	43.18	46.22
26	19.57	17.15	15.24	18.28	72	48.78	46.36	44.45	47.49
28	20.84	18.42	16.51	19.55	74	50.05	47.63	45.72	48.76
30	22.11	19.69	17.78	20.82	76	51.32	48.90	46.99	50.03
32	23.38	20.96	19.05	22.09	78	52.59	50.17	48.26	51.30
34	24.65	22.23	20.32	23.36	80	53.86	51.44	49.53	52.57
36	25.92	23.50	21.59	24.63	82	55.13	52.71	50.80	53.84
38	27.19	24.77	22.86	25.90	84	56.40	53.98	52.07	55.11
40	28.46	26.04	24.13	27.17	86	57.67	55.25	53.34	56.38
42	29.73	27.31	25.40	28.44	88	58.94	56.52	54.61	57.65
44	31.00	28.58	26.67	29.71	90	60.21	57.79	55.88	58.92
46	32.27	29.85	27.94	30.98	92	61.48	59.06	57.15	60.19
48	33.54	31.12	29.21	32.25	94	62.75	60.33	58.42	61.46
50	34.81	32.39	30.48	33.52	96	64.02	61.60	59.69	62.73
52	36.08	33.66	31.75	34.79	98	65.29	62.87	60.96	64.00
54	37.35	34.93	33.02	36.06	100	66.56	64.14	62.23	65.27

Material and Finish

1. Housing: Thermoplastic (UL94V-0), Black.
2. Terminal: Sq. 0.40mm Copper Alloy, Gold Plating.

Electrical Characteristics

1. Current Rating: 1.0 Amp. Max..
2. Dielectric Withstand Voltage: 600V AC RMS for 60Seconds.
3. Insulation Resistance: 1000M Ohms Min. at 500V DC.

Mechanical Characteristics

1. Operating Temperature: -55°C ~ +105°C

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±



ORDER INFORMATION

PAB-V16PC-2Xxx-LF
SERIES | LEADFREE
180°SMT | 2X05:10 WAY
1.6mm HIGH | 2X50:100 WAY
CAP POST

DESCRIPTION: 1.27*1.27mm Box Header PCB Surface Mount Dual Rows