



MATERIAL:

- 1.1 Housing: thermoplastic high temp. UL94V-0; Color: Black.
- 1.2 Terminal: Copper Alloy.
- 1.3 Shell: Stainless Steel or SPCC

ELECTRICAL:

- 2.1 Current rating: 1.0A AC/DC.
- 2.2 Voltage: 30V Max.
- 2.3 Contact resistance: 60 milliohms Max.
- 2.4 Insulation resistance: 100 Megohms Min.
- 2.5 Withstanding voltage: 100V AC/Minute.
- 2.6 Temperature range: -25°C to +85°C.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PJECTION



ORDER INFORMATION

MISB-SDM2B-5B-LF

SERIES | | | | | LEADFREE
5 PIN B TYPE
B LAYOUT
METAL FOOT
DIP 180°
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Micro USB 5Pin Female DIP VERTICAL TYPE