



	7.0φ BACK SHELL
	6.0φ BACK SHELL
⊗	5.0φ BACK SHELL (STANDARD)
	COVER DIM.

TABLE A

MATERIAL:

- A.COVER: PE+2L
- B.SHELL: ABS
- C.METAL SHIELD:
BRASS NICKEL PLATED
- D.HOUSING: NYLON66+GF
- E.CONTACT:
BRASS SILVER PLATED

SPECIFICATIONS:

- 1.RATING:11V AC 1A MAX
OR 12V DC 2A MAX.
- 2.INSULATION RESISTANCE:
50M OHM MIN AT 500V DC.
3. DIELECTRIC STRENGTH:
500V AC / 1 MINUTE.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

P PROJECTION



ORDER INFORMATION

MDA-P-xx-LF
SERIES | LEADFREE
04~08 WAY
MALE

DESCRIPTION: Mini Din plug Ass'y Type