

## SPECIFICATIONS

### Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze or Brass

### Electrical

Current Rating : 1 Amp

Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.

Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C

Terminated with 1.27mm pitch flat ribbon cable.

| POSITION | A      | B     | C     |  | E     |
|----------|--------|-------|-------|--|-------|
| 10       | 43.06  | 15.50 | 10.16 |  | 22.36 |
| 14       | 48.14  | 20.58 | 15.24 |  | 27.44 |
| 16       | 50.68  | 23.12 | 17.78 |  | 29.98 |
| 20       | 55.76  | 28.20 | 22.86 |  | 35.06 |
| 26       | 63.38  | 35.82 | 30.48 |  | 42.68 |
| 34       | 73.54  | 45.98 | 40.64 |  | 52.84 |
| 40       | 81.16  | 53.60 | 48.26 |  | 60.46 |
| 50       | 93.86  | 66.30 | 60.96 |  | 73.16 |
| 60       | 106.56 | 79.00 | 73.66 |  | 85.86 |
| 62       | 109.10 | 81.54 | 76.20 |  | 88.40 |
| 64       | 111.64 | 84.08 | 78.74 |  | 90.94 |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

E-C2FE-xx-LF  
SERIES | LEADFREE  
10~64WAY  
FULL EAR  
TWO TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: