

1. 備注:

- 1). 外規無缺料, 破損, 髒污
- 2). 材料: NYLON 66 UL 94V-0
- 3). 顏色: 本色

2. Dimension:

Circuits	Part No.	Dimension:(mm)		
		A	B	C
3	VU-H-03	13.55±0.25	7.92±0.20	11.54±0.20
4	VU-H-04	17.51±0.25	11.88±0.20	15.50±0.20
5	VU-H-05	21.47±0.30	15.84±0.25	19.46±0.25
7	VU-H-07	29.39±0.30	23.76±0.25	27.38±0.25

3. Specifications:

Current rating:	10A AC/DC
Voltage rating:	250V AC/DC
Temperature range:	-25°C to +85°C
Insulation resistance:	1000MΩ Min
Withstanding voltage:	1500V AC/DC
Terminal/Housing Retention Force:	2.5kgf Min

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

VU-H-xx-LF  
SERIES | LEADFREE  
03~07 AWG  
MALE TERMINAL

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: