

RECOMMENDED PCB LAYOUT

	Dim A	Dim B
2-6p	±0.15	±0.15
7-12p	±0.25	±0.25
13-18p	±0.30	±0.30
19-24p	±0.40	±0.40

N = Number of poles

Dim A=Nx5.0

Dim B=(N-1)x5.0

Material:

- Item ③ Male contact pin: Copper Tin plated
- Item ⑥ Termine (housing): Thermoplastic (UL94V-0)

- Electrical: cULus /VDE /TUV
- Voltage rating: 300V/300V/300V
- Current rating: 20A/20A/20A
- Withstanding Voltage: 1.6 KV/2.5KV/2.5KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: cULus VDE TÜV

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1


.XXX ±

DATE

ANG ±

SIZE A4

PJECTION



ORDER INFORMATION

TBH050-PR-xx-LF

SERIES | | LEADFREE
02-24WAY
DIP 90°
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: