

Recomended PCB Layout

### Specifications

Contact Resistance:  $\leq 30m$  max. at DC  
 100mA  
 Insulator Resistance: 1000M min. at DC  
 500V  
 Current Rating: 5 AMP  
 Dielectric Withstanding  
 Voltage: AC 1000V For 1 minute  
 Operating Temperature:  $-55^{\circ}C \sim +105^{\circ}C$   
 Contact: Brass  
 Housing: PBT & 30% Glass Fiber (UL  
 94V-0)

### Dimension

Positon	A	B	C
9	16.92	24.99	30.81
15	25.50	33.32	39.14
25	38.96	47.04	53.04
37	55.42	63.50	69.32

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X.  $\pm$   
 .X  $\pm 0.10$   
 .XX  $\pm 0.05$   
 .XXX  $\pm$   
 ANG  $\pm$



### ORDER INFORMATION

DDM-P-xx-LF  
 SERIES | LEADFREE  
 09-37WAY  
 MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: D-SUB DIP STRAIGHT TYPE W/O METAL REAT SHELL