

- NOTE:
- SAFETY:
 - RATING: 0.5A/250Vac.
 - CONTACT RESISTANCE: 30mOhm MAX.
 - INSULATION RESISTANCE: 100Mohm MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 100Vac/1minute.
 - DURABILITY: 10,000cycles.
 - MATERIAL:
 - PIN: PHOSPHOR BRONZE.
 - HOUSING: NYLON COLOR: TABLE A Δ
 - LATCH: STAINLESS #304.
 - SHELL: STAINLESS #304. Δ
 - COVER: NYLON 66 COLOR: BLACK. Δ
 - PLATING:
 - PIN: GOLD 15u" MIN ON CONTACT AREA, TIN 100u" MIN ON SOLDER TAILS, UNDERPLATED NICKEL OVER ALL 60u" MIN.

TABLE A

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

MISB-PA-5B-LF
SERIES | LEADFREE
5 PIN B TYPE
ASSEMBLY
MALE

DESCRIPTION: MICRO USB 5PIN(M) B TYPE