


ELECTRIC FUNCTION	DETECT SWITCH
WITHOUT CARD	OPEN
CARD INSERTED	CLOSED



### MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK  
SHELL: STAINLESS STEEL  
TERMINAL: PHOSPHOR BRONZE, GOLD PLATED ON CONTACT AREA TIN PLATING ON SOLDER TAIL

### SPECIFICATION

CURRENT RATING: 0.5 AMP MAX  
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
CONTACT RESISTANCE: 30m OHMS MAX  
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
OPERATION TEMPERATURE: -40°C~+85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
**煜倫股份有限公司**

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ± 3°

PJECTION



ORDER INFORMATION

SCV-W2525XB-06-LF

SERIES      LEADFREE  
90°SMT      06WAY  
OPEN SWITCH  
NON POST  
BODY HIGH 2.5mm  
PAD TO PAD 25.54mm

DESCRIPTION: SIM CARD, 6PIN, PCB MOUNT, SMT, METAL SHIELD, FEMALE, HINGE TYPE WITH SWITCH

www.morethanall.com