



A-A SECTION



8	Contact Terminals	Brass	Silver Ptd.	5
7	5P180 Housing	ABS		1
6	Spring Ring	Steel	Nickel Ptd.	1
5	Setscrew	Steel	Nickel Ptd.	1
4	"T" Holder	Steel	Nickel Ptd.	1
3	Strain Boot	PVC		1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

**Specifications
rating :**

100V AC 1A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

DAMS-PA-05-LF

SERIES | LEADFREE
| 05 WAY
| ASSEMBLY
MALE

DESCRIPTION: