

**MATERIALS**  
 HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK  
 TERMINAL: PHOSPHOR BRONZE, GOLD PLATED ON CONTACT AREA TIN PLATING ON SOLDER TAIL

**SPECIFICATION**  
 CURRENT RATING: 0.5 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -25°C~+85°C


PIN NO.	NAME
C1	Vcc
C2	RST
C3	CLK
C5	GND
C6	Vpp
C7	I/O

**RoHS Compliant**

TOLERANCES ARE



DRAWING BY CY		X, ± .X ± 0.30 .XX ± 0.20 .XXX ± 0.10 ANG ± 3°
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PJECTION	



**ORDER INFORMATION**

SCV-W2525P-06-LF  
 SERIES | LEADFREE  
 90°SMT | 06WAY  
 POST  
 BODY HIGH 2.5mm  
 PAD TO PAD 25.54mm

DESCRIPTION: SIM CARD, 6PIN, PCB MOUNT, SMT, HINGE TYPE, WITH POST

煜倫股份有限公司

www.morethanall.com