


PCB LAYOUT
(BOTTOM VIEW)

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S. T:0.30	GOLD PLATED	2
2	INSERT RING	PBT G.F.	BLACK,RED	2
3	INSULATOR	PBT G.F.	WHITE	2
4	CENTER PIN	BRASS T:0.25	GOLD PLATED	2
5	FRAME	C.R.S. T:0.60	GOLD PLATED	1



Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
 Durability (Life Test): 4000 Cycles.
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0 Kg.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.38

.X ± 0.25

.XX ± 0.13

.XXX ± 0.05

ANG ±

P PROJECTION



ORDER INFORMATION

RCAB1-JR52E0KRG01-03-LF

SERIES JACK
DIP 90°
5.2mm

LEADFREE
03WAY

GOLD
RED
BLACK
NON EAR

DESCRIPTION: