


Specifications

Current Rating:1Amp  
 Insulation Resistance:1000MΩMin.  
 Dielectric Withstanding Voltage:300VAC  
 Contact Resistance:20mΩMax.  
 Operating Temperature:-40°C to +105°C  
 Materials

⚠ Contact Material:Phosphor Bronze  
 Insulator Material:High Temperature Thermoplastic, UL 94V-0 LCP or the equivalent material ⚠

Recommended P.C.Board  
 Layout  
 (Tolerance:±0.05)



**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. ± 0.30  
 .X ± 0.25  
 .XX ± 0.15  
 .XXX ± 0.10  
 ANG ±



**ORDER INFORMATION**

YA-D4423-2Xxx-LF  
 SERIES | LEADFREE  
 2X02:04WAY  
 2X50:100WAY  
 DIP 180° | DIP 2.3mm  
 HIGH 4.40mm

DESCRIPTION:1.27 FEMALE HEADER DUAL ROWS DIP TYPE CONNECTOR