



NO	DESCRIPTION	MATERIAL	FINISH	QTY
8	NUT	BRASS	NICKEL	1
7	WASHER	PHOSPHOR BRONZE	NICKEL	1
6	SOLDER TAIL	BRASS WIRE	TIN LEAD	1
5	MOUNTING POST	BRASS	TIN LEAD	1
4	INSULATOR	PE-606	NONE	1
3	HOUSING	PBT	WHITE	1
2	BODY	ZINC ALLOY	NICKEL	1
1	CENTER CONTACT	PHOSPHOR BRONZE	GOLD	1



RECOMMENDED MOUNTING HOLE  
 MAXIMUM PANEL THICKNESS: 5.5MM  
 RECOMMENDED MOUNTING TORQUE:  
 12 INCH-POUNDS MAX


RoHS Compliant

TOLERANCES ARE

0.5-5	=±0.2
6-30	=±0.4
30-120	=±0.6
120-315	=±1
315-1000	=±1.6
1000-2000	=±2.4



ORDER INFORMATION



DESCRIPTION: 75 OHM BNC VERTICAL PCB/PANEL MOUNT JACK

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

PJECTION