

HOUSING+CONTACT+SPRING+SHELL+LOCKING COLLAR+O-RING


Contact position arrangement and specifications					
Contact configuration		Withstanding voltage	300V AC	Operating temperature range	-25c to +85c
		Voltage rating	30V AC, 42V DC	Insulation resistance	1000MΩ
		Current rating	2A		
		Contact resistance	15MΩ		
MATERIAL					
HOUSING	PPS UL94V-0/BLACK	PLUG SHELL	ZINC ALLOY	LOCKING COLLAR	ZINC ALLOY
CONTACT	PHOSPHOR BRONZE	SPRING 0.5*10.7	STAINLESS STEEL	O-RING Ø9.9 L0.9	EPDM/BLACK
O-RING Ø11.5 L1.0	EPDM/BLACK	O-RING Ø10.75 L3.4	NBR/BLACK	鎖緊環(TIGHTENING COLLAR)	PPS/棕色
Clamps	BRASS	STRAIN RELIEF COLLAR	NYLON66/WHITE	SHIELDING Ø10.4 L5.2 T0.15	PHOSPHOR BRONZE
BACK SHELL	ZINC ALLOY				
FINISH					
CONTACT	GOLD FLASH	PLUG SHELL	NICKEL	SHIELDING Ø10.4 L5.2 T0.15	NICKEL
BACK SHELL	NICKEL	LOCKING COLLAR	NICKEL		

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		X, ± .X ± 0.20 .XX ± 0.10 .XXX ± 0.05 ANG ± 1°
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PPOJECTION	



ORDER INFORMATION

DAS12-JA-12-LF
 SERIES | LEADFREE
 12 WAY
 ASSEMBLY
 FEMALE

DESCRIPTION: DIN 12PIN(F) LF 線端