

COMMENDED PCB LAYOUT
TOL:(±0.05)

Notes:

Material: Phosphor Bronze(C5191-H)
SIMM Card Connector,With

Physical:

Housing: Lcp UL 94V-0

Contact: Selective Gold Flash

FINISH : Gold plated on contact area & 100 μ'
Min. Tin/lead or Sn only plated on soldering
end over 50 μ' Min. Nickel

Specifications:

Voltage Current rating: 1A. 50V AC

Insulation Resistance: 1000Mohm Min

Contact Withstanding Voltage:

AC 500V For 1 Minute

Temperteure Rating: -40° To +85°

Durability: 10000 Cycles Min

IR Re-Flow:260°C 15Sec Max

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.25
.XX ± 0.15
.XXX ± 0.10
ANG ±



ORDER INFORMATION

SCT-W1028X-06-LF
SERIES | LEADFREE
| 06WAY
| NON POST
| HIGH 2.8mm
| PAD TO PAD 10.1mm
| 90°SMT

DESCRIPTION: