



Follow RoHs Standard

1. Dielectric strength: AC 500V/1 minute.
2. Insulation resistance: 100MΩ Min. (at 500V DC)
3. Contact resistance: 30mΩ Max.
4. Rating: 18V, 2A.

7	190-067	外殼	ABS		1
6	170-184	彈片 B	黃銅	鍍鎳	1
5	170-185	彈片 A	黃銅	鍍鎳	1
4	176-003	墊片	PBT(HB)		1
3	119-106	鎖牙套管	黃銅	鍍鎳	1
2	119-105	螺帽	黃銅	鍍鎳	1
1	150-217	5.5X2.1DC 插頭		鍍鎳	1
項目	圖面號碼	零件名稱	材料	處理	數量

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±

DATE

.XXX±

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

DCP-AS-5525S-LF
SERIES | ID: 2.5Ø | LEADFREE
SHORT
OD: 5.5Ø
SCREW
ASSEMBLY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 5.5X2.1DC 插頭(內鎖牙裝配式) 9.5mm