



PIN OUTS

P1	P2
OPEN	1 RED (红)
OPEN	2 BLACK (黑)

包装方式: 10PCS/把。

用PE膜包裹, 再依照外箱大小装入防水袋。

ELECTRONIC TEST:

- 100% TEST, (Open, Short, Miss Wire).
- Conduct Resistance: 5Ω/max.
- Insulation Resistance: 10MΩ/min.
- Hi-Pot: 300v dc/10ms.

PART LIST: 本产品均符合"ROHS"环保标准, 用的材料均为相当品。

4	PVC 45P 黑色外模		KG/K
3	DC JACK 5.5*2.5 母頭.	1	PCS
2	MICRO USB BM:GOLD FLASH CONNECTOR, NICKEL PLAIED SHELL, PLASTLC:BLACK	1	PCS
1	UL 2464 24AWG*2C OD : 3.5mm 外被黑色 L=1030MM.	1	PCS
ITEM	STANDARD SPECIFICATION	Q' TY	UNIT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

DCX1-552524-F40N-LF

SERIES | LEADFREE
1030mm
FEMALE
24AWG
5.5X2.5mm

DESCRIPTION: MICRO TO DC5525母头 CABLE BLACK L=1030MM

www.morethanall.com