

Material

- Item a Terminal body; Thermoplastic (UL94V-0)
- Item b Terminal cover; Thermoplastic (UL94V-0)
- Item c Terminal screw ; Steel Zinc plating "-" slot type
- Item d Clampage; Steel/steel Zinc plated
- Item e Terminal body; Steel, Zinc plating
- Item f Solder pin; Copper, Tin plated

Electrical

- Voltage rating: 300VAC
- Current rating: 30A
- Wire range:
- Solid wire(AWG): 10-24
- Stranded wire(AWG): 10-24
- Torque(Lb-In): 4.3
- Screw: M3
- Wire strip length: 15-16mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec

△ Critical dimension: ▽

Poles	01	02	03	04	05	06	07	08
Dim L	7.85	14.2	20.55	26.9	33.25	39.6	45.95	52.3
Dim B		6.35	12.70	19.05	25.40	31.75	38.10	44.45
TOL	±0.10		±0.15		±0.20		±0.25	
Poles	09	10	11	12	13	14	15	16
Dim L	58.65	65.0	71.35	77.7	84.05	90.4	96.75	103.1
Dim B	50.80	57.15	63.50	69.85	76.20	82.55	88.90	95.25
TOL	±0.30		±0.35		±0.40			

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.10


DATE

.XXX ±

ANG ± 1°

SIZE A4

P PROJECTION



ORDER INFORMATION

TBH063-R26B-xx-LF

SERIES

LEADFREE

01~16WAY

TWO LEG

HIGH 26.0mm

DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: