

A	COLOR	B
9	RED	1
7	WHITE	2
5	GREEN	3
3	BLACK	4

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL2725 #28*1PR(WHITE, GREEN)+#28*2C(RED, BLACK) +AEB JACKET:BLACK OD:Ø3.5 USB2.0	1PCS	E238846
2	HOUSING:	PVK-H-2X05	1PCS	E115256
3	TERMINAL:	PVK-T-22	4PCS	
4	KEY:	PVK-KBK-10	1PCS	E115256
5	HOUSING:	ZHQ-H-04	1PCS	E179987
6	TERMINAL:	ZHQ-T-24	4PCS	
7	SHRINK TUBE:	5Ø*20mm BLACK F32	2PCS	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±

PJECTION



ORDER INFORMATION

PVKZHQ-B050428R1-F16N-LF

SERIES

LEADFREE  
406.4mm  
FEMALE TO FEMALE  
ROUND CABLE  
28 AWG  
10 TO 04 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS'Y