

A	COLOR	B
1	YELLOW	4
2	BLACK	3
3	BLACK	2
4	YELLOW	1

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #20 YELLOW	2PCS	E108485
	WIRE:	UL1007 #20 BLACK	2PCS	E108485
2	HOUSING:	MIF-SH-1X04	2PCS	E115256
3	TERMINAL:	MIF-FT-20	8PCS	
4				
5				
6				
7				

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±


.X ±

.XX ±

.XXX ±

ANG ±

PJECTION



ORDER INFORMATION

MIFX2-040420W2-Fxxx-LF

SERIES

LEADFREE

12N:12 INCH

60C:600mm

FEMALE TO FEMALE

04 TO 04 WAY

WIRE

20 AWG

DESCRIPTION: CABLE ASS"Y